



बढैयाताल गाउँपालिका  
गाउँ निकाय कार्यालय  
लुम्बिनी प्रदेश नेपाल  
मैनापोखर बढैया

दररेट कायमको लागि दररेट पेश गर्ने बारेको सार्वजनिक सुचना ।

पहिलो पटक सूचना मिति २०८३।०६।१६

यस कार्यालयबाट तपसिलका कार्यहरु सिलबन्दी दररेटको माध्यमबाट दररेट कायम गराउनु पर्ने भएकोले इच्छुक इजाजत प्राप्त फर्मबाट निम्न शर्तहरुको अधिनमा रही रितपूर्वकको सिलबन्दी दररेट पेशको लागि आव्हान गरिएको छ शर्तहरु

१. यस कार्यालयमा मौजुदा सुचीमा दर्ता रहेका फर्महरुले आ व २०८२/०८३ सम्मको नविकरण गरेको इजाजतपत्र, मूल्य अभिवृद्धि कर दर्ता प्रमाणपत्र, करचुक्ता प्रमाणपत्रको प्रतिलिपी संलग्न राखी प्रथम पटक सूचना प्रकाशित भएको मितिले ३(तीन) दिन भित्र कार्यालय समयमा सिलबन्दी दररेट फारम बढैयाताल गाउँपालिकाको कार्यालयमा पेश गर्नुहुन जानकारी गराइन्छ ।

तपसिल

| SN | Description       | Specification | QTY | Unit | Rate | Amount |
|----|-------------------|---------------|-----|------|------|--------|
| 1  | Access Point (AP) | Model         | 1   |      |      |        |
|    |                   | Type          |     |      |      |        |
|    |                   | Wi-Fi         |     |      |      |        |
|    |                   | Frequency     |     |      |      |        |
|    |                   | Speed         |     |      |      |        |
|    |                   | Antennas      |     |      |      |        |
|    |                   | LAN Ports     |     |      |      |        |
|    |                   | PoE           |     |      |      |        |
|    |                   | Features      |     |      |      |        |
| 2  | Access Point (AP) | Model         | 1   |      |      |        |
|    |                   | Type          |     |      |      |        |
|    |                   | Wi-Fi         |     |      |      |        |
|    |                   | Frequency     |     |      |      |        |
|    |                   | Speed         |     |      |      |        |
|    |                   | Total Speed   |     |      |      |        |
|    |                   | MIMO          |     |      |      |        |
|    |                   | Antennas      |     |      |      |        |
|    |                   | LAN Ports     |     |      |      |        |

अञ्जन बारु  
प्रमुख प्रशासकिय अधिकृत



|   |                          |                                                                        |                               |   |  |  |  |                                                                                    |
|---|--------------------------|------------------------------------------------------------------------|-------------------------------|---|--|--|--|------------------------------------------------------------------------------------|
|   |                          | PoE                                                                    | 802.3af/at PoE/PoE+           |   |  |  |  |  |
|   |                          | Mounting                                                               | Ceiling / Wall                |   |  |  |  |                                                                                    |
|   |                          | Dimensions                                                             | 194 × 194 × 35 mm             |   |  |  |  |                                                                                    |
| 3 | Switch POE Power Adapter | Model                                                                  |                               |   |  |  |  |                                                                                    |
|   |                          | Type                                                                   | Passive PoE Injector          |   |  |  |  |                                                                                    |
|   |                          | LAN Port                                                               | 1 × Gigabit (1000Base-T)      |   |  |  |  |                                                                                    |
|   |                          | Output Power                                                           | 15.6 W                        |   |  |  |  |                                                                                    |
|   |                          | Output Voltage                                                         | 52 V DC @ 0.3 A               |   |  |  |  |                                                                                    |
|   |                          | Input Voltage                                                          | 100–240 V AC, 50/60 Hz        |   |  |  |  |                                                                                    |
|   |                          | Input Current                                                          | Max. 0.5 A                    |   |  |  |  |                                                                                    |
|   |                          | PoE Powering                                                           | 2-Pair, Pins 4/5 (+), 7/8 (-) | 1 |  |  |  |                                                                                    |
| 4 | Switch POE Power Adapter | Model                                                                  |                               |   |  |  |  |                                                                                    |
|   |                          | Type                                                                   | 1-Port Passive PoE Injector   |   |  |  |  |                                                                                    |
|   |                          | Port                                                                   | 1 × Gigabit 1000Base-T        |   |  |  |  |                                                                                    |
|   |                          | PoE Power                                                              | 31.2 W                        |   |  |  |  |                                                                                    |
|   |                          | Output                                                                 | 52 V DC, 0.6 A                |   |  |  |  |                                                                                    |
|   |                          | Input                                                                  | 100–240 V AC, 50/60 Hz        |   |  |  |  |                                                                                    |
|   |                          | PoE                                                                    | Passive PoE+, 2-pair          | 1 |  |  |  |                                                                                    |
| 5 | Cat 6 cable              | • 50 m carton UTP CAT6, power over Ethernet, compatible with one cable |                               |   |  |  |  |                                                                                    |
|   |                          | • High-purity oxygen-free copper(99.97%) conductor .                   |                               |   |  |  |  |                                                                                    |
|   |                          | • PVC Outer Sheath of min. average thickness 0.7mm(0.03).              |                               |   |  |  |  |                                                                                    |
|   |                          | • 23AWG of Diameter 0.57 mm ± 0.02mm (0.02 ± 0.0007).                  |                               | 1 |  |  |  |                                                                                    |
| 6 | 8 Port gigabite          | • Unmanaged access switch.                                             |                               |   |  |  |  |                                                                                    |
|   |                          | • All gigabit Ethernet ports.                                          |                               |   |  |  |  |                                                                                    |
|   |                          | • Plug and play.                                                       |                               |   |  |  |  |                                                                                    |
|   |                          | • Easy to operate                                                      |                               |   |  |  |  |                                                                                    |
|   |                          | • 16G Switching Capacity.                                              |                               |   |  |  |  |                                                                                    |
|   |                          | • 11.904Mpps Packet Forwarding Rate.                                   |                               |   |  |  |  |                                                                                    |
|   |                          | • 2k MAC Table Size.                                                   |                               | 1 |  |  |  |                                                                                    |
| 7 | Fiber 6 core             | 6 Core, Single Mode (SM)                                               |                               |   |  |  |  |                                                                                    |
|   |                          | G.652D, 9/125 μm                                                       |                               | 1 |  |  |  |                                                                                    |

अर्जुन शर्मा  
प्रमुख प्रशासकिय अधिकृत

|    |                          |                                                                                             |                                                                                             |   |  |  |
|----|--------------------------|---------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|---|--|--|
| S  | 01 Cable                 | Outdoor, PE/HDPE Jacket                                                                     |                                                                                             |   |  |  |
|    |                          | FRP/Steel Strength Member                                                                   |                                                                                             |   |  |  |
|    |                          | 1310/1550 nm                                                                                |                                                                                             |   |  |  |
|    |                          |                                                                                             | 1                                                                                           |   |  |  |
| 9  | Tiffin box               | • High quality plastics compact and lite weight. Easy to install and Long life              |                                                                                             |   |  |  |
|    |                          | • Applications :Optical Fiber Network,Telecommunications networks,FTTH, FTTx,FTTP,OSP,CATV. | 1                                                                                           |   |  |  |
| 10 | Listic                   | 40/42 mm                                                                                    | 1                                                                                           |   |  |  |
|    | MATISX Dual IRIS Scanner | Brand:                                                                                      |                                                                                             |   |  |  |
|    |                          | Category                                                                                    | Biometric Devices                                                                           |   |  |  |
|    |                          | Capture Type                                                                                | Dual IRIS Capture                                                                           |   |  |  |
|    |                          | IRIS Diameter                                                                               | 210 Pixel                                                                                   |   |  |  |
|    |                          | Pixel Resolution                                                                            | 20 Pixel/mm                                                                                 |   |  |  |
|    |                          | Image Margins                                                                               | Left & Right $\geq 0.5 \times$ IRIS Diameter, Top & Bottom $\geq 0.25 \times$ IRIS Diameter |   |  |  |
|    |                          | Pixel Depth                                                                                 | 8 Bits/Pixel (256 Gray Level)                                                               |   |  |  |
|    |                          | Sensor SNR                                                                                  | 40 dB                                                                                       |   |  |  |
|    |                          | Capture Mode                                                                                | Auto Capture with Built-in Quality Check (incorporates NIST quality considerations)         |   |  |  |
|    |                          | Illumination                                                                                | Near Infra Red (NIR)                                                                        | 1 |  |  |



*[Signature]*

अर्जुन थारु

प्रमुख प्रशासकीय अधिकृत

अर्जुन थारु

प्रमुख प्रशासकीय अधिकृत